

HYOSUNG HEAVY INDUSTRIES		INDUCTION MOTOR DATA SHEET		PROJECT No. 1675	
				MODEL No. 24TE-FFEB	
				L-SPEC No. D1ML8755	
SHEET 1 OF 1		CUSTOMER			
FOR INFORMATION		JOB NO.		ITEM No.	
SERVICE		SITE		QUANTITY	
GENERAL DATA			PERFORMANCE DATA		
FRAME No.		200L		OUTPUT 30 kW	
TYPE		TE-F		POLES 6 P	
ENCLOSURE		TE		ROTOR TYPE SQUIRREL CAGE	
COOLING METHOD		FC(IC411)		STARTING METHOD DIRECT ON LINE	
INSULATION CLASS		F CLASS		PHASE 3 PHASE	
TEMP. RISE AT FULL LOAD			FREQUENCY 60 Hz		
RES. METHOD		80 K (at S.F:1.0)		SPEED (AT FULL LOAD) 1180 r/min	
RATING		S1		PRIMARY	
LOCATION		INDOOR		VOLTAGE 380 V	
ALTITUDE		LESS THAN 1000 m		NO LOAD CURRENT 27.7 A	
HUMIDITY		LESS THAN 80 %		FULL LOAD CURRENT 59.1 A	
AMBIENT TEMP.		40 °C		LOCKED-ROTOR CURRENT 680 %	
EXPLOSION PROOF TYPE		N/A		EFFICIENCY	
MOUNTING		V1		AT 1/2 LOAD 91.1 %	
BEARING TYPE		ANTI-FRICTION		AT 3/4 LOAD 93.1 %	
NDE/DE BRG. No.		6212ZC3 / 6313ZC3		AT FULL LOAD 94.1 %	
BRG. LUBRICATION		MOBIL Polyrex EM		POWER FACTOR	
PROTECTION GRADE		IP55		AT 1/2 LOAD 67.0 %	
SERVICE FACTOR		1.15		AT 3/4 LOAD 77.0 %	
DRIVE		DIRECT COUPLED		AT FULL LOAD 82.0 %	
SHAFT			TORQUE		
EXTENSION		SINGLE		FULL LOAD 24.8 kg-m	
EXTERNAL THRUST		N/A		243.3 N-m	
NOISE LEVEL(MEAN VALUE AT 1m FROM MOTOR)			LOCKED ROTOR 160 %		
NO-LOAD		N/A		BREAKDOWN 260 %	
VIBRATION		N/A		MOTOR GD² 2.583 kg-m²	
NUMBER OF CONSECUTIVE STARTS		N/A		MAX LOAD GD² AT MOTOR SHAFT 191.2 kg-m²	
ROTATION(VIEWED FROM DE)		C.C.W		MOTOR APPROX. WEIGHT 325 kg	
ACCESSORIES (OPTIONAL)			PAINTING 0.5PB 3.2/4.4 (URETHANE)		
SUBMITTAL DRAWINGS					
TEMPERATURE DETECTOR			OUTLINE DIMENSION ES1AS48714		
WINDING NO			CONDUIT BOX & COVER ES1B100804		
TYPE -			SPEED-TORQUE & CURRENT CURVE D1ML8755		
BEARING NO			THERMAL LIMIT & TIME-CURRENT CURVE D1ML8755		
TYPE -			LOAD vs POWER FACTOR & EFFICIENCY D1ML8755		
SPACE HEATER NO			<REMARKS>		
RATING -			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
APPLICATION STANDARDS IEC60034-1, ISO 3746			2. PREMIUM EFFICIENCY TYPE MOTOR		
<NOTE>					
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARD.			REV. NO DATE PREPARED CHECKED APPROVED		
2. EXCEPT FOR STATEMENTS SPECIFIED ON THIS SHEET, ANYTHING ELSE SHALL BE IN ACCORDANCE WITH MAKER STANDARD			1 2025-09-22 S.U.LEE J.H.CHA Y.J.PARK		
3. THE TEMPERATURE MEASURED AT BEARING HOUSING DOES NOT EXCEED 105°C.					

