

HYOSUNG HEAVY INDUSTRIES		INDUCTION MOTOR DATA SHEET		PROJECT No. 2467	
				MODEL No. 24EFFEB	
				L-SPEC No. D1ML20424	
SHEET 1 OF 1		CUSTOMER			
FOR INFORMATION		JOB NO.		ITEM No.	
SERVICE		SITE		QUANTITY	
GENERAL DATA			PERFORMANCE DATA		
FRAME No.		250S		OUTPUT 75 kW	
TYPE		EF		POLES 4 P	
ENCLOSURE		TE		ROTOR TYPE SQUIRREL CAGE	
COOLING METHOD		FC(IC411)		STARTING METHOD DIRECT ON LINE	
INSULATION CLASS		F CLASS		PHASE 3 PHASE	
TEMP. RISE AT FULL LOAD			FREQUENCY 60 Hz		
RES. METHOD		80 K (at S.F:1.0)		SPEED (AT FULL LOAD) 1785 r/min	
RATING		S1		PRIMARY	
LOCATION		INDOOR		VOLTAGE 380 V	
ALTITUDE		LESS THAN 1000 m		NO LOAD CURRENT 59.0 A	
HUMIDITY		LESS THAN 80 %		FULL LOAD CURRENT 144.8 A	
AMBIENT TEMP.		40 °C		LOCKED-ROTOR CURRENT 650 %	
EXPLOSION PROOF TYPE		Ex d IIB T4		EFFICIENCY	
MOUNTING		B3		AT 1/2 LOAD 92.4 %	
BEARING TYPE		ANTI-FRICTION		AT 3/4 LOAD 94.4 %	
NDE/DE BRG. No.		6313C3 / 6316C3		AT FULL LOAD 95.4 %	
BRG. LUBRICATION		MOBIL Polyrex EM		POWER FACTOR	
PROTECTION GRADE		IP55		AT 1/2 LOAD 67.5 %	
SERVICE FACTOR		1.0		AT 3/4 LOAD 77.5 %	
DRIVE		DIRECT COUPLED		AT FULL LOAD 82.5 %	
SHAFT			TORQUE		
EXTENSION		SINGLE		FULL LOAD 40.9 kg-m	
EXTERNAL THRUST		N/A		401.2 N-m	
NOISE LEVEL(MEAN VALUE AT 1m FROM MOTOR)			LOCKED ROTOR 170 %		
NO-LOAD		N/A		BREAKDOWN 220 %	
VIBRATION		N/A		MOTOR GD² 4.799 kg-m²	
NUMBER OF CONSECUTIVE STARTS		N/A		MAX LOAD GD² AT MOTOR SHAFT 189.5 kg-m²	
ROTATION(VIEWED FROM DE)		C.C.W		MOTOR APPROX. WEIGHT 795 kg	
ACCESSORIES (OPTIONAL)			PAINTING 0.5PB 3.2/4.4 (URETHANE)		
SUBMITTAL DRAWINGS					
TEMPERATURE DETECTOR			OUTLINE DIMENSION ES1AS30118		
WINDING NO			CONDUIT BOX & COVER ES1B100919		
TYPE -			SPEED-TORQUE & CURRENT CURVE D1ML20424		
BEARING NO			THERMAL LIMIT & TIME-CURRENT CURVE D1ML20424		
TYPE -			LOAD vs POWER FACTOR & EFFICIENCY D1ML20424		
SPACE HEATER NO			<REMARKS>		
RATING -			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
APPLICATION STANDARDS IEC60034-1, ISO 3746			2. PREMIUM EFFICIENCY TYPE MOTOR		
<NOTE>					
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARD.			REV. NO		
2. EXCEPT FOR STATEMENTS SPECIFIED ON THIS SHEET, ANYTHING ELSE SHALL BE IN ACCORDANCE WITH MAKER STANDARD			DATE		
3. THE TEMPERATURE MEASURED AT BEARING HOUSING DOES NOT EXCEED 105°C.			PREPARED		
			CHECKED		
			APPROVED		
			1		
			2025-09-23		
			S.U.LEE		
			J.H.CHA		
			Y.J.PARK		

Data are subject to change without notice.(설계 개선 및 제작 환경에 따라 사전 공지 없이 특성 사양치 변경될 수 있음)

A4(210X297)