

HYOSUNG HEAVY INDUSTRIES		INDUCTION MOTOR DATA SHEET		PROJECT No. 2469	
				MODEL No. 24EFFEB	
				L-SPEC No. D1ML20811	
SHEET 1 OF 1		CUSTOMER			
FOR INFORMATION		JOB NO.		ITEM No.	
SERVICE		SITE		QUANTITY	
GENERAL DATA			PERFORMANCE DATA		
FRAME No.		280S		OUTPUT 110 kW	
TYPE		EF		POLES 4 P	
ENCLOSURE		TE		ROTOR TYPE SQUIRREL CAGE	
COOLING METHOD		FC(IC411)		STARTING METHOD DIRECT ON LINE	
INSULATION CLASS		F CLASS		PHASE 3 PHASE	
TEMP. RISE AT FULL LOAD			FREQUENCY 60 Hz		
RES. METHOD		80 K (at S.F:1.0)		SPEED (AT FULL LOAD) 1785 r/min	
RATING		S1		PRIMARY	
LOCATION		INDOOR		VOLTAGE 380 V	
ALTITUDE		LESS THAN 1000 m		NO LOAD CURRENT 57.3 A	
HUMIDITY		LESS THAN 80 %		FULL LOAD CURRENT 201.7 A	
AMBIENT TEMP.		40 °C		LOCKED-ROTOR CURRENT 640 %	
EXPLOSION PROOF TYPE		Ex d IIB T4		EFFICIENCY	
MOUNTING		B3		AT 1/2 LOAD 92.8 %	
BEARING TYPE		ANTI-FRICTION		AT 3/4 LOAD 94.8 %	
NDE/DE BRG. No.		6316C3 / 6319C3		AT FULL LOAD 95.8 %	
BRG. LUBRICATION		MOBIL Polyrex EM		POWER FACTOR	
PROTECTION GRADE		IP55		AT 1/2 LOAD 71.5 %	
SERVICE FACTOR		1.0		AT 3/4 LOAD 81.5 %	
DRIVE		DIRECT COUPLED		AT FULL LOAD 86.5 %	
SHAFT			TORQUE		
EXTENSION		SINGLE		FULL LOAD 60 kg-m	
EXTERNAL THRUST		N/A		588.6 N-m	
NOISE LEVEL(MEAN VALUE AT 1m FROM MOTOR)			LOCKED ROTOR 100 %		
NO-LOAD		N/A		BREAKDOWN 200 %	
VIBRATION		N/A		MOTOR GD² 9.213 kg-m²	
NUMBER OF CONSECUTIVE STARTS		N/A		MAX LOAD GD² AT MOTOR SHAFT 259 kg-m²	
ROTATION(VIEWED FROM DE)		C.C.W		MOTOR APPROX. WEIGHT 1035 kg	
ACCESSORIES (OPTIONAL)			PAINTING 0.5PB 3.2/4.4 (URETHANE)		
SUBMITTAL DRAWINGS					
TEMPERATURE DETECTOR			OUTLINE DIMENSION ES1AS30122		
WINDING			CONDUIT BOX & COVER ES1B100919		
TYPE			SPEED-TORQUE & CURRENT CURVE D1ML20811		
BEARING			THERMAL LIMIT & TIME-CURRENT CURVE D1ML20811		
TYPE			LOAD vs POWER FACTOR & EFFICIENCY D1ML20811		
SPACE HEATER			NO		
RATING			-		
APPLICATION STANDARDS			IEC60034-1, ISO 3746		
<NOTE> 1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARD. 2. EXCEPT FOR STATEMENTS SPECIFIED ON THIS SHEET, ANYTHING ELSE SHALL BE IN ACCORDANCE WITH MAKER STANDARD 3. THE TEMPERATURE MEASURED AT BEARING HOUSING DOES NOT EXCEED 105°C.			<REMARKS> 1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE. 2. PREMIUM EFFICIENCY TYPE MOTOR		
REV. NO		DATE		PREPARED	
1		2025-09-23		S.U.LEE	
CHECKED		APPROVED			
J.H.CHA		Y.J.PARK			