

HYOSUNG HEAVY INDUSTRIES		INDUCTION MOTOR DATA SHEET		PROJECT No. 2653	
				MODEL No. 24EF-FFEB	
				L-SPEC No. D1ML20606	
SHEET 1 OF 1		CUSTOMER			
FOR INFORMATION		JOB NO.		ITEM No.	
SERVICE		SITE		QUANTITY	
GENERAL DATA			PERFORMANCE DATA		
FRAME No.		280M		OUTPUT 110 kW	
TYPE		EF-F		POLES 6 P	
ENCLOSURE		TE		ROTOR TYPE SQUIRREL CAGE	
COOLING METHOD		FC(IC411)		STARTING METHOD DIRECT ON LINE	
INSULATION CLASS		F CLASS		PHASE 3 PHASE	
TEMP. RISE AT FULL LOAD			FREQUENCY 60 Hz		
RES. METHOD		80 K (at S.F:1.0)		SPEED (AT FULL LOAD) 1195 r/min	
RATING		S1		PRIMARY	
LOCATION		INDOOR		VOLTAGE 380 V	
ALTITUDE		LESS THAN 1000 m		NO LOAD CURRENT 88.1 A	
HUMIDITY		LESS THAN 80 %		FULL LOAD CURRENT 212.7 A	
AMBIENT TEMP.		40 °C		LOCKED-ROTOR CURRENT 710 %	
EXPLOSION PROOF TYPE		Ex d IIB T4		EFFICIENCY	
MOUNTING		V1		AT 1/2 LOAD 92.8 %	
BEARING TYPE		ANTI-FRICTION		AT 3/4 LOAD 94.8 %	
NDE/DE BRG. No.		6316C3 / 6319C3		AT FULL LOAD 95.8 %	
BRG. LUBRICATION		MOBIL Polyrex EM		POWER FACTOR	
PROTECTION GRADE		IP55		AT 1/2 LOAD 67.0 %	
SERVICE FACTOR		1.0		AT 3/4 LOAD 77.0 %	
DRIVE		DIRECT COUPLED		AT FULL LOAD 82.0 %	
SHAFT			TORQUE		
EXTENSION		SINGLE		FULL LOAD 89.7 kg-m	
EXTERNAL THRUST		N/A		880.0 N-m	
NOISE LEVEL(MEAN VALUE AT 1m FROM MOTOR)			LOCKED ROTOR 120 %		
NO-LOAD		N/A		BREAKDOWN 170 %	
VIBRATION		N/A		MOTOR GD² 17.034 kg-m²	
NUMBER OF CONSECUTIVE STARTS		N/A		MAX LOAD GD² AT MOTOR SHAFT 679 kg-m²	
ROTATION(VIEWED FROM DE)		C.C.W		MOTOR APPROX. WEIGHT 1100 kg	
ACCESSORIES (OPTIONAL)			PAINTING 0.5PB 3.2/4.4 (URETHANE)		
SUBMITTAL DRAWINGS					
TEMPERATURE DETECTOR			OUTLINE DIMENSION ES1AS16724		
WINDING NO			CONDUIT BOX & COVER ES1B100919		
TYPE -			SPEED-TORQUE & CURRENT CURVE D1ML20606		
BEARING NO			THERMAL LIMIT & TIME-CURRENT CURVE D1ML20606		
TYPE -			LOAD vs POWER FACTOR & EFFICIENCY D1ML20606		
SPACE HEATER NO			<REMARKS>		
RATING -			1. ABOVE ALL DATA ARE CALCULATED AT 100% VOLTAGE.		
APPLICATION STANDARDS IEC60034-1, ISO 3746			2. PREMIUM EFFICIENCY TYPE MOTOR		
<NOTE>					
1. THESE DATA ARE ONLY DESIGN VALUES AND SHALL BE GUARANTEED WITH TOLERANCE OF APPLICATION STANDARD.			REV. NO		
2. EXCEPT FOR STATEMENTS SPECIFIED ON THIS SHEET, ANYTHING ELSE SHALL BE IN ACCORDANCE WITH MAKER STANDARD			DATE		
3. THE TEMPERATURE MEASURED AT BEARING HOUSING DOES NOT EXCEED 105°C.			PREPARED		
			CHECKED		
			APPROVED		
			1		
			2025-09-23		
			S.U.LEE		
			J.H.CHA		
			Y.J.PARK		

Data are subject to change without notice.(설계 개선 및 제작 환경에 따라 사전 공지 없이 특성 사양치 변경될 수 있음)

A4(210X297)