

1
2

[illegible]

Technical drawing of a mechanical part. The drawing shows a circular base with a diameter of 39.5. A rectangular feature is mounted on top of the circle, with a width of 14 and a height of 5.5. The total height of the part is 9.

HIGH RATIO NKV105 +KF172	CAPACITY (Kw)	0.4KW				WEIGHT (Kg)
	REDUCTION RATIO	1/300	1/400	1/500	1/600	
	OUTPUT R.P.M	6	4.5	3.6	3	57
	Max.TORQUE Kgf.m	53.7	71.6	71.6	70	

TOOTH CHAMFERING		MODULE					표기법 및 일반 공차	
		2	5-15	15			각도 : ±0.2°	6 - 30 : 120
HQ. T	C1	0.2	0.5	1.0			CHAMFER: C1.0	30 - 120 : 315
	C2	1.0	1.5	2.0			FILLET: R1.0	120 - 315 : 1000
HC & HQ. I	C1	0.5	1.0	2.0			마무리: 	315 - 1000 : 1000
	C2	2.0	3.0	5.0			M=8(R0.1-1M)	M=8-15(R0.3M)

OUT LINE DWG							
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T	REMARK	
TITLE SPEC.	HIGH RATIO GEARED MOTOR V105+KF172 1/2HP 4P 삼성		CUSTOMER				
	RATIO=1/300~1/600		NEW STANDARD TYPE				
DRAWN	KSS	SCALE	1 / 1	UNIT	mm		
DESIGN	YHH	DATE	2018.04.04	PROJECTION			
CHECKED	REF. No.					REV. No.	△
APPROVED	DRAWING No.		KGM-KF172+V105-HT-0.5-00-000				
 (주) 케이지엠 KOREA GEARED MOTOR							