

1
2



TOOTH CHAMFERING		MODULE						표기와 일반 공차			
		0.5	5-15	15				각도 : 0.2°	6 ~ 30 : ±0.1	CHAMFER: C1.0	30 ~ 120 : ±0.15
HQ. T	C1	0.2	0.5	1.0				마무리:  315 ~ 1000 : ±0.3 1000 이상 : ±0.5			
	C2	1.0	1.5	2.0							
HC & HQ. I	C1	0.5	1.0	2.0				마무리:  315 ~ 1000 : ±0.3 1000 이상 : ±0.5			
	C2	2.0	3.0	5.0							
					M<R(0.1-1M)	M=8-15(R(0.3M))	M>15(R(0.3M))				

OUT LINE DWG						
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T	REMARK
TITLE SPEC.	HIGH RATIO GEARED MOTOR V172+KF270 3HP 4P		CUSTOMER STANDARD TYPE			
	RATIO=1/150~1/200					
DRAWN	KSS	SCALE	1 / 1	UNIT	mm	
DESIGN	YHH	DATE	2018.04.05	PROJECTION		
CHECKED		REF. No.			REV. No.	
APPROVED		DRAWING No.	KGM-KF270+V172-HF-03-00-000			
			(주) 케이지엠 KOREA GEARED MOTOR			