

A
B
C
D
E
F



(주)MAX.TORQUE; 56.5Kg-m이하로 사용

TOOTH CHAMFERING		MODULE						표기법 및 일반 공차		표기법 및 일반 공차
		5	5-15	15				기어	기어	
HQ. T	C1	0.2	0.5	1.0				각도: ±0.2°	6 ~ 30 : ±0.1	표기법 및 일반 공차
	C2	1.0	1.5	2.0				CHAMFER: C1.0	30 ~ 120 : ±0.15	
HC & HQ. I	C1	0.5	1.0	2.0				FILLET: R1.0	120 ~ 315 : ±0.2	표기법 및 일반 공차
	C2	2.0	3.0	5.0				M<R(0.10~1M)	M=R-15(R0.3M)	
					M<R(0.10~1M)	M=R-15(R0.3M)	M=15(R0.3M)		1000 이상 : ±0.5	

OUT LINE DWG							
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T	REMARK	
TITLE SPEC.	GEARED MOTOR KF181 10HP 4P IE3 I=1/15~1/20 OUT LINE DWG		CUSTOMER STANDARD TYPE				
DRAWN	KSS	SCALE	1 / 1	UNIT	mm		
DESIGN	YHH	DATE	2019.09.03	PROJECTION			
CHECKED		REF. No.			REV. No.		
APPROVED		DRAWING No.	KGM-KF181-HT-10-00-00				
(주) 케이지엠 KOREA GEARED MOTOR							