

[illegible]

KV270	CAPACITY (Kw)	3.7Kw 4P		WEIGHT (Kg)
	REDUCTION RATIO	1/100	1/120	
	OUTPUT R.P.M	18	15	185

TOOTH CHAMFERING		MODULE					표기와 일반 공차	
		5	5-15	15			각도 : $\pm 0.2^\circ$	6 - 30 : ± 0.1
HQ. T	C1	0.2	0.5	1.0			CHAMFER: C1.0 30 - 120 : ± 0.1	
	C2	1.0	1.5	2.0			FILLT: R1.0 120 - 315 : ± 0.1	
HC & HQ. I	C1	0.5	1.0	2.0				
	C2	2.0	3.0	5.0	1000 이상 : ± 0.1			

	OUT LINE DWG								
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T	REMARK			
TITLE SPEC.	GEARED MOTOR		CUSTOMER						
	KV270 SHP 4P IE3 I=1/100-1/120		STANDARD TYPE						
	OUT LINE DWG								
DRAWN	KSS	SCALE	N / S	UNIT	mm				
DESIGN	YHH	DATE	2019.08.12	PROJECTION					
CHECKED		REF. No.				REV.			
APPROVED		DRAWING No.	KGM-KV270-YT-05-00-000						
			(주) 케이지엠 KOREA GEARED MOTOR						