

B

C

D

E

F

OUTPUT SHAFT

TOOTH CHAMFERING		MODULE						표기와 일반 공차	
		0.5	5-15	15				각도 : $\pm 0.2^\circ$	6 - 30
HQ. T	C1	0.2	0.5	1.0				CHAMFER: C1.0	30 - 120
	C2	1.0	1.5	2.0				FILLET: R1.0	120 - 315
HC & HQ. I	C1	0.5	1.0	2.0				마무리: 	1315 - 1000
	C2	2.0	3.0	5.0				M=8(R0.1-1M)	M=8-15(R0.3M)

	OUT LINE DWG								
No.	DESCRIPTION		SPECIFICATION		MAT'L		Q'TY	W/T	REMARK
TITLE SPEC.	GEARED MOTOR				CUSTOMER				
	KF270 10HP 4P IE3 I=1/40-1/50				STANDARD TYPE				
	OUT LINE DWG								
DRAWN	KSS	SCALE	N / S		UNIT		mm		
DESIGN	YHH	DATE	2019.11.11		PROJECTION				
CHECKED	REF. No.						REV. No.		
APPROVED	DRAWING No.		KGM-KF270-HT-10-00-00						
			(주) 케이지엠 KOREA GEARED MOTOR						