

			INDUCTION MOTOR DATA SHEET					
SHEET 1 OF 1			CUSTOMER				PROJECT#	
FOR PROPOSAL			MODEL NO.		IKM-0752P		ITEM NO.	
EFFICIENCY CLASS : IE3 (PREMIUM)			JOB NO.				QUANTITY	
GENERAL DATA				PERFORMANCE DATA				
FRAME NO.		80M		OUTPUT		1		HP
TYPE		B5				0.75		KW
ENCLOSURE		TOTALLY ENCLOSED		POLES		2		P
COOLING METHOD		FC		ROTOR TYPE		SQUIRREL CAGE		
FREQUENCY (HZ)		60 HZ		STARTING METHOD		DOL		
PHASE		3 PHASE						
INSULATION CLASS		F CLASS		VOLTAGE		220/380		V
TEMPERTURE RISE AT FULL LOAD				NO LOAD CURRENT		-		A
		RES. METHOD	80 deg	FULL LOAD CURRENT		3.6/2.1		A
		THERMO. METHOD	℃	STARTING CURRENT		18.43 / 11.08		A
LOCATION		INDOOR						
ALTITUDE		1000 m		EFFICIENCY				
HUMIDITY		80%				AT 1/2 LOAD		69.2 %
AMBIENT TEMPERATURE		- 10~40 ℃				AT 3/4 LOAD		74.5 %
RATING		CONT.				AT FULL LOAD		77 %
MOUNTING		-						
BEARING TYPE		BALL / BALL		POWER FACTOR				
LOAD/UNLOAD BRG.NO		6204ZZ / 6203ZZ				AT 1/2 LOAD		50 %
BEARING LUBRICATION		GREASE				AT 3/4 LOAD		62.7 %
PROTECTION GRADE		IP 55				AT FULL LOAD		86 %
SERVICE FACTOR		1.15						
				SPEED (AT FULL LOAD)		3470		RPM
CONDENSER								
		START	-	TORQUE				
		RUN	-			FULL LOAD		0.21 kg-m
ACCESSORIES (OPTIONAL)						LOCKED ROTOR		0.38 kg-m
		TEMPERATURE DETECTOR	-			BREAKDOWN		0.42 kg-m
		SPACE HEATER	-					
		SLIDE BASE	-	NOISE LEVEL		73		Db(A)
				MOTOR APPROX. WEIGHT				KG
				PAINTING		5Y		
REMARKS								
TEFC:Totally Enclosed FanCooled				DATE	PREPD BY	CHKD BY	APPRD BY	
				2022.10.06				