



M5*0.8
M6* 1
M8*1.25
M10*1.5
M12*1.75
M16* 2
M18*2.5
M20*2.5
M22*2.5
M24*3



TOOTH CHAMFERING		M O D U L E						표기와 일반 공차	
		5	5~15	15				각도 : $\pm 0.2^\circ$	6 ~ 30 : ± 0.1
HQ. T	C1	0.2	0.5	1.0				CHAMFER: C1.0	30 ~ 120 : ± 0.1
	C2	1.0	1.5	2.0				FILLET: R1.0	120 ~ 315 : ± 0.1
HC & HQ. I	C1	0.5	1.0	2.0				마무리:	315 ~ 1000 : ± 0.1
	C2	2.0	3.0	5.0				M<8(R0.1~1M)	M=8~15(R0.3M)

	OUT LINE DWG								
No.	DESCRIPTION		SPECIFICATION		MAT'L	Q'TY	W/T	REMARK	
TITLE SPEC.	KDH GEARED MOTOR 15KW 4P IE3 I=1/90 OUTLINE DIMENSION				CUSTOMER KD H3503 STANDARD TYPE				
	DRAWN		KSS	SCALE	1 / 1		UNIT	mm	
	DESIGN		YHH	DATE	2020.11.30		PROJECTION		
CHECKED			REF. No.	KD H3503			REV No.		
ARRRIVED			DRAWING No.	KDH3503-20-90-OD					
 (주) 케이지엠 KOREA GEARED MOTOR									