





NO.	REVISION	DATE	DESIGNED	CHECKED	APPROVED
△					
△					



KD-HL H2252	CAPACITY(Kw)	3.7kw4P		2.2kw6P	
	REDUCTION RATIO	1/25	1/30	1/25	1/30
	OUTPUT R.P.M	72	60	48	40
	WEIGHT (Kg)	105			

TOOTH CHAMFERING	MODULE				표기와 일반 공차
	5	5-15	15		
HQ. T	C1	0.2	0.5	1.0	각도 : ±0.2° 6 - 30 : ±0.1°
	C2	1.0	1.5	2.0	
HC & HQ. I	C1	0.5	1.0	2.0	CHAMFER: C1.0 30 - 120: ±0.15 FILLET: R1.0 120 - 315 : ±0.2
	C2	2.0	3.0	5.0	
M<8(R0.1-1M) M=8-15(R0.3M) M>15(R0.3M)					마무리: ▽ 315 - 1000 : ±0.3 1000 이상 : ±0.5

OUT LINE DWG					
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T
TITLE SPEC.		KD-HL LINE POWER 3.7KW 4P I=1/25~1/30		CUSTOMER KD-HL H2252	
DESIGN		DATE 2018.09.07		PROJECTION	
CHECKED		REF. No. KD-HL H2252		REV. No.	
APPROVED		DRAWING No. KDHL-H2252-05-25-90-00			

M5±0.8
M6±1
M8±1.25
M10±1.5
M12±1.75
M16±2
M18±2.5
M20±2.5
M22±2.5
M24±3