

M5*0.8
M6* 1
M8*1.25
M10*1.5
M12*1.75
M16* 2
M18*2.5
M20*2.5
M22*2.5
M24*3



KD H3502 I.E.C	CAPACITY(Kw)	30kw4P			19,22kw6P		
	REDUCTION RATIO	1/10	1/15	1/20	1/10	1/15	1/20
	OUTPUT R.P.M	180	120	90	120	80	60
	WEIGHT (Kg)	370					

TOOTH CHAMFERING		M O D U L E						표기와 일반 공차	
		5	5~15	15				각도 : $\pm 0.2^\circ$	6 ~ 30 : ± 0.1
HQ. T	C1	0.2	0.5	1.0				CHAMFER: C1.0	30 ~ 120 : ± 0.15
	C2	1.0	1.5	2.0				FILLET: R1.0	120 ~ 315 : ± 0.2
HC & HQ. I	C1	0.5	1.0	2.0					315 ~ 1000 : ± 0.3
	C2	2.0	3.0	5.0					M<B(R0.1~1M)

()내의 치수는 다소 변경될수 있음.

	OUT LINE DWG							
No.	DESCRIPTION		SPECIFICATION		MAT'L	Q'TY	W/T	REMARK
TITLE SPEC.	KDH GEARED MOTOR IEC 30KW 4P I=1/10~1/20			CUSTOMER KD H3502 I.E.C TYPE				
	OUTLINE DIMENSION							
DRAWN	KSS	SCALE	1 / 1	UNIT	MM			
DESIGN	YHH	DATE	2019.02.22	PROJECTION				
CHECKED	REF. No.		KD H3502	REV. No.				
APPROVED	DRAWING No.		KDH3502-IEC-40-10-20-0D					



(주) 케이지엠
KOREA GEARED MOTOR