


M5*0.8
M6* 1
M8*1.25
M10*1.5
M12*1.75
M16* 2
M18*2.5
M20*2.5
M22*2.5
M24*3



KD H4202 I.E.C	CAPACITY(Kw)		37kw4P			30kw6P		
	REDUCTION RATIO	1/10	1/15	1/20	1/10	1/15	1/20	
	OUTPUT R.P.M	180	120	90	120	80	60	
	WEIGHT (Kg)	580						

TOOTH CHAMFERING		M O D U L E						표기와 일반 공차	
		5	5~15	15				각도 : $\pm 0.2^\circ$	6 - 30 : ± 0.1
HQ. T	C1	0.2	0.5	1.0				CHAMFER: C1.0	30 - 120 : ± 0.15
	C2	1.0	1.5	2.0				FILLET: R1.0	120 - 315 : ± 0.2
HC & HQ. I	C1	0.5	1.0	2.0				마우리 : ∇	315 - 1000 : ± 0.3
	C2	2.0	3.0	5.0				M<B(R0.1-1M)	M=8-15(R0.3M)



	OUT LINE DWG								
No.	DESCRIPTION		SPECIFICATION		MAT'L	Q'TY	W/T	REMARK	
TITLE SPEC.	KDH GEARED MOTOR IEC 37KW 4P I=1/10~1/20			CUSTOMER KD H4202					
	OUTLINE DIMENSION			I.E.C TYPE					
DRAWN	KSS	SCALE	1 / 1		UNIT		MM		
DESIGN	YHH	DATE	2019.10.11		PROJECTION				
CHECKED		REF. No.	KD H4202		REV.				
ARRORVED		DRAWING No.	KDH4202-IEC-50-10~20-00		REV. No.				



(주) 케이 지 엠
KOREA GEARED MOTOR