






NO.	REVISION	DATE	DESIGNED	CHECKED	APPROVED
△					
△					



()내의 치수는 MOTOR 변경에 따른 치수비와 GEAR S.F 결정시 치수 확정됨.

M5*0.8
M6* 1
M8*1.25
M10*1.5
M12*1.75
M16* 2
M18*2.5
M20*2.5
M22*2.5
M24*3

TOOTH CHAMFERING	MODULE				표기외 일반 공차
	5	5-15	15		
HQ. T	C1	0.2	0.5	1.0	각도 : ±0.2°
	C2	1.0	1.5	2.0	6 - 30 : ±0.1
HC & HQ. I	C1	0.5	1.0	2.0	CHAMFER: C1.0
	C2	2.0	3.0	5.0	30 - 120: ±0.15
					FILLET: R1.0
					120 - 315 : ±0.3
					마무리: ▽
					315 - 1000 : ±0.3
					1000 이상 : ±0.5

OUT LINE DWG					
No.	DESCRIPTION	SPECIFICATION	MAT'L	Q'TY	W/T
TITLE SPEC.		CUSTOMER			
		BEVEL HELICAL GEARED KB07 HSM OUT LINE DWG		STANDARD TYPE	
DRAWN	KSS	SCALE	1 / 1	UNIT	mm
DESIGN	YHH	DATE	2021.02.04	PROJECTION	☺
CHECKED		REF. No.			
ARRROVED		DRAWING No.	KGM-KB07-HSM-00-00-00	REV. No.	△



(주) 케이 지 엠
KOREA GEARED MOTOR